

ALTA, Co. Stefanikova 41 602 00 Brno Czech Republic Phone: +420 541 550 111 Fax: +420 541 550 555 e-mail: office@alta.cz http://www.alta.cz

Registered Nr.: 60735244

Prerov 22nd October 2015

LLK- International Industrial OEM Dept. Manager Mr. Stepan Kirillov

Re: LUKOIL lubricants use in ALTA equipment

Dear Mr. Kirillov,

This letter is the official approval of LUKOIL lubricants, which meet the requirements for ALTA mining equipment: crushers, screens, conveyors, etc.

a) Lubricants for cone crushers

For the application in cone crushers gear oil is used in the viscosity classes VG100 and VG150. The use of LUKOIL STEELO 100 (for winter) or LUKOIL STEELO 150 (for summer) is permitted.

There are appropriate approvals.

b) Hydraulic oils for cone, jaw and rotary crushers

For the application in cone, jaw and rotary crushers hydraulic oil is used in the viscosity class VG46.

The use of LUKOIL GEYSER ST 46 and LUKOIL GEYSER ZF 46 is permitted. There are appropriate approvals.

c) Grease for cone, jaw and rotary crushers and vibratory screens

For the application in cone, jaw and rotary crushers and vibratory screens grease is used in the appropriate indexes EP 2-160.

The use of LUKOIL Polyflex EP2-160 is permitted.

There are appropriate approvals.

d) Lubricants for gearboxes in conveyors and other equipment

For the application in the gearboxes of conveyors and other equipment synthetic gear oil is used in the viscosity class VG220.

The use of LUKOIL STEELO Premium 220 is permitted.

There are appropriate approvals.

e) <u>Lubricants for bearings in screens VTK 200x500/4, 200x600/2, 200x600/4 and 200x700/2</u> For the application in the bearings of screens gear oil is used in the viscosity class VG68.

The use of LUKOIL STEELO 68 is permitted.

There are appropriate approvals.

Ing Jiri Janik

Chief of Commercial Dept.